

	RHINO Power Supplies	Aust\$
PSB24-060-P	RHINO switching power supply, 24 VDC (adjustable), 2.5A (60W) output, 85-264 VAC / 120-375 VDC universal input, plastic case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$39
PSB24-060	RHINO switching power supply, 24 VDC (adjustable), 2.5A (60W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$49
PSB24-120	RHINO switching power supply, 24 VDC (adjustable), 5A (120W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$91
PSB24-240	RHINO switching power supply, 24 VDC (adjustable), 10A (240W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$165
PSB24-480	RHINO switching power supply, 24 VDC (adjustable), 20A (480W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$247
PSB12-015-P	RHINO switching power supply, 12 VDC (adjustable), 1.25A (15W) output, 85-264 VAC / 120-375 VDC universal input, plastic case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$31
PSB12-030-P	RHINO switching power supply, 12 VDC (adjustable), 2.5A (30W) output, 85-264 VAC / 120-375 VDC universal input, plastic case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$34
PSB12-060	RHINO switching power supply, 12 VDC (adjustable), 5A (60W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$53
PSB12-100	RHINO switching power supply, 12 VDC (adjustable), 8.3A (100W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$81
PSB24-060-3	RHINO switching power supply, 24 VDC (adjustable), 2.5A (60W) output, 320-575 VAC 3-phase universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CSA certified, CE marked.	\$85
PSB24-120-3	RHINO switching power supply, 24 VDC (adjustable), 5A (120W) output, 320-575 VAC 3-phase universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CSA certified, CE marked.	\$109
PSB24-240-3	RHINO switching power supply, 24 VDC (adjustable), 10A (240W) output, 320-575 VAC 3-phase universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CSA certified, CE marked.	\$182
PSB24-480-3	RHINO switching power supply, 24 VDC (adjustable), 20A (480W) output, 320-575 VAC 3-phase universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CSA certified, CE marked.	\$259
PSB-CVR	Replacement terminal covers for all RHINO PSB series power supplies	\$7
PSS24-035	RHINO enclosed panel mount switching power supply, 24 VDC (adjustable), 1.46A (35W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$29
PSS24-050	RHINO enclosed panel mount switching power supply, 24 VDC (adjustable), 2.1A (50W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$32
PSS24-100	RHINO enclosed panel mount switching power supply, 24 VDC (adjustable), 4.17A (100W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$43
PSS12-035	RHINO enclosed panel mount switching power supply, 12 VDC (adjustable), 2.9A (35W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$29
PSS12-050	RHINO enclosed panel mount switching power supply, 12 VDC (adjustable), 4.1A (50W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$32
PSS12-100	RHINO enclosed panel mount switching power supply, 12 VDC (adjustable), 8.3A (100W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$43

	RHINO Metal Case Slim-Line Power Supplies and Accessories	Aust\$
PSM12-078S	Switching power supply, 12 VDC (adjustable), 6A, 78W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$185
PSM24-090S	Switching power supply, 24 VDC (adjustable), 3.75A, 90W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$145
PSM24-090S-N	NEC Class 2 switching power supply, 24 VDC (adjustable), 3.75A, 90W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$190
PSM12-156S	Switching power supply, 12 VDC (adjustable), 13A, 156W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$230
PSM24-180S	Switching power supply, 24 VDC (adjustable), 7.5A, 180W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$220
PSM24-360S	Switching power supply, 24 VDC (adjustable), 15A, 360W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$329
PSM24-600S	Switching power supply, 24 VDC (adjustable), 25A, 600W output, DIN rail mounting, slim, metal case, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$489
	redundancy module	Aust\$
PSM24-REM360S	Redundancy module, 24 VDC, 15A, 360W, for use with PSM24 power supplies. Alarm contact for operation monitoring. Inputs are hot swappable and can be loaded to 15A each.	\$225
	battery control module	
PSM24-BCM360S	Battery control module, 24 VDC, 15A, 360W for charging external lead-acid battery. Contacts provided for input and output operation, and battery level. Remote on/off contact and temperature sensing circuit included.	\$220
	buffer module	
PSM24-BFM600S	Buffer module, 24 VDC (adjustable), 25A, 600W, for use with PSM power supplies. Provides protection against brownouts or voltage dips on input power. Hold-up time is up to 4 seconds at 1.2A. Operation LED indicator on front panel.	\$320
	mounting bracket	Aust\$
PSM-PANEL1	Panel mounting bracket for 78W, 90W, 156W, 180W PSM power supplies	\$24
PSM-PANEL2	Panel mounting bracket for 360W, 600W PSM power supplies	\$34
PSM-PK1	Replacement plug kit for PSM series with 72W and 90W outputs	\$11
PSM-PK2	Replacement plug kit for PSM series with 156W, 180W and 360W outputs	\$11
PSM-PK3	Replacement plug kit for PSM series redundancy module PSM24-REM360S	\$8
PSM-PK4	Replacement plug kit for PSM series buffer module PSM24-BFM600S	\$10
PSM-PK5	Replacement plug kit for PSM series battery control module PSM24-BCM360S	\$35
PSM-TS	Temperature sensor accessory for PSM series battery control module PSM24-BCM360S	\$30
PSM-JC01	Replacement link cable for PSM series redundancy module PSM24-REM360S and battery control module PSM24-BCM360S	\$9

	RHINO Plastic Case Slim-Line Power Supplies	Aust\$
PSP05-020S	Switching power supply, 5 VDC (adjustable), 4A 20W output, DIN rail or panel mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950, and CE.	\$115
PSP12-024S	Switching power supply, 12 VDC (adjustable), 2A, 24W output, DIN rail or panel mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950, and CE.	\$110
PSP24-024S	Switching power supply, 24 VDC (adjustable), 1A (24W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, foldback short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$85
PSP12-060S	Switching power supply, 12 VDC (adjustable), 4A (60W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$145
PSP24-060S	Switching power supply, 24 VDC (adjustable), 2.5A (60W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$125
PSP12-120S	Switching power supply, 12 VDC (adjustable), 8A (120W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$225
PSP24-120S	Switching power supply, 24 VDC (adjustable), 5A (120W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$210
PSP24-024C	Switching power supply, 24 VDC (adjustable), 1A (24W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, foldback short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$90
PSP12-060C	Switching power supply, 12 VDC (adjustable), 4A (60W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$159
PSP24-060C	Switching power supply, 24 VDC (adjustable), 2.5A (60W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$125
PSP12-120C	Switching power supply, 12 VDC (adjustable), 8A (120W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$250
PSP24-120C	Switching power supply, 24 VDC (adjustable), 5A (120W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$210
PSP24-240S	Switching power supply, 24 VDC (adjustable), 10A (120W) output, DIN rail mounting, slim, plastic case with detachable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, UL60950 and CE.	\$270
PSP24-REM240S	Redundancy module, 24 VDC, 15A, 360W, for use with PSP24 power supplies. Alarm contact for operation monitoring. Inputs are hot swappable and can be loaded to 15A each.	\$70

	PS Series Metal Case DC Power Supplies	Aust\$
PS12-050D	Switching power supply, 12 VDC, 4A (50W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-264 VAC input, constant current short circuit protection, UL508, 1950 & CE.	\$157
PS12-075D	Switching power supply, 12 VDC, 6A (75W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$226
PS24-050D	Switching power supply, 24 VDC, 2A (50W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-264 VAC input, constant current short circuit protection, UL508, 1950 & CE.	\$142
PS24-075D	Switching power supply, 24 VDC, 3A (75W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$161
PS24-150D	Switching power supply, 24 VDC, 6A (150W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$253
PS24-300D	Switching power supply, 24 VDC, 12A (300W) DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$324
PS24-500D	Switching power supply, 24 VDC, 20A (500W) DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC input, constant current short circuit protection, UL508, 1950 & CE.	\$558
PS24-600D	Switching power supply, 24 VDC, 24A (600W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$552
PS24-PLUG-1	Replacement terminal plug kit for PS12-050D, PS24-050D, PS24-075D and PS24-150D, 1 each input & output plug	\$15
PS24-PLUG-3	Replacement terminal plug kit for PS24-300D, 1 each input & output plug	\$20
PS24-PLUG-5	Replacement terminal plug kit for PS24-500D, 1 each input & output plug	\$23
	DC to DC Converters	Aust\$
PSP05-DC24-5	DC to DC converter, 18-75 VDC in, 5 VDC at 5.0 amps out, DIN rail mounting, slim plastic case with detachable screw terminal connector	\$116
PSP12-DC24-2	DC to DC converter, 18-75 VDC in, 12 VDC at 2.0 amps out, DIN rail mounting, slim plastic case with detachable screw terminal connector	\$116
PSP24-DC24-1	DC to DC converter, 18-75 VDC in, 24 VDC at 1.0 amp out, DIN rail mounting, slim plastic case with detachable screw terminal connector	\$110
PSP24-DC12-1	DC to DC converter, 9.5-18 VDC in, 24 VDC at 1.0 amp out, DIN rail mounting, slim plastic case with detachable screw terminal connector	\$115

Control Transformers and Accessories		Aust\$
PH50PG	12x24 VAC 50/60 Hz control transformer, 50VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$79
PH75PG	12x24 VAC 50/60 Hz control transformer, 75VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$65
PH100PG	12x24 VAC 50/60 Hz control transformer, 100VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$75
PH150PG	12x24 VAC 50/60 Hz control transformer, 150VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$95
PH250PG	12x24 VAC 50/60 Hz control transformer, 250VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$125
PH350PG	12x24 VAC 50/60 Hz control transformer, 350VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$145
PH500PG	12x24 VAC 50/60 Hz control transformer, 500VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$180
PH750PG	12x24 VAC 50/60 Hz control transformer, 750VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$255
PH1000PG	12x24 VAC 50/60 Hz control transformer, 1 kVA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$280
PFK1	Primary side fuse kit for control transformers to 100VA	\$13
PFK2	Primary side fuse kit for control transformers from 150VA to 250VA	\$13
PFK3	Primary side fuse kit for control transformers from 350VA to 1KVA	\$13
FG1	Finger-safe cover for 50VA UNFUSED control transformers, includes one cover for primary side or secondary side	\$20
FG2	Finger-safe cover for 75VA and 100VA UNFUSED control transformers, includes one cover for primary side or secondary side	\$20
FGF1	Finger-safe cover for 50VA FUSED control transformers, includes one cover for primary side or secondary side	\$10
FGF2	Finger-safe cover for 75VA and 100VA FUSED control transformers, includes one cover for primary side or secondary side	\$10
FG3	Finger-safe cover for all 150VA and 250VA FUSED and UNFUSED control transformers, includes one cover for primary side or secondary side	\$10
FG4	Finger-safe cover for all 350VA and 750VA FUSED and UNFUSED control transformers, includes one cover for primary side or secondary side.	\$10
FG5	Finger-safe cover for all 1kVA FUSED and UNFUSED control transformers, includes one cover for primary side or secondary side	\$10
Hammond 480V Encapsulated Transformers		Aust\$
C1F007LES	240x120 VAC 60 Hz encapsulated transformer, 7.5kVA, 480x240 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$840
C1F010LES	240x120 VAC 60 Hz encapsulated transformer, 10kVA, 480x240 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$968
C1F015LES	240x120 VAC 60 Hz encapsulated transformer, 15kVA, 480x240 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$1,251
C1F025LES	240x120 VAC 60 Hz encapsulated transformer, 25kVA, 480x240 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$1,552
Hammond 277V Encapsulated Transformers		Aust\$
C1FC10WE	240x120 VAC 60 Hz encapsulated transformer, 100VA, 277x240x208x120 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R heavy duty enclosure, cULus 1604, T3C temperature classification	\$118
C1FC25WE	240x120 VAC 60 Hz encapsulated transformer, 250VA, 277x240x208x120 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R heavy duty enclosure, cULus 1604, T3C temperature classification	\$144
C1FC50WE	240x120 VAC 60 Hz encapsulated transformer, 500VA, 277x240x208x120 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R heavy duty enclosure, cULus 1604, T3C temperature classification	\$168
C1F1C0WES	240x120 VAC 60 Hz encapsulated transformer, 1kVA, 277x240x208x120 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$254
C1F002WES	240x120 VAC 60 Hz encapsulated transformer, 2kVA, 277x240x208x120 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$395
C1F003WES	240x120 VAC 60 Hz encapsulated transformer, 3kVA, 277x240x208x120 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$509
C1F005WES	240x120 VAC 60 Hz encapsulated transformer, 5kVA, 277x240x208x120 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$722

	Hammond 220V Encapsulated Transformers	Aust\$
C1FC25XE	240x120 VAC 60 Hz encapsulated transformer, 250VA, 220/208/200/190x440/416/400/380 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R heavy duty enclosure, cULus 1604, T3C temperature classification	\$158
C1FC50XE	240x120 VAC 60 Hz encapsulated transformer, 500VA, 220/208/200/190x440/416/400/380 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R heavy duty enclosure, cULus 1604, T3C temperature classification	\$184
C1F1C0XES	240x120 VAC 60 Hz encapsulated transformer, 1kVA, 220/208/200/190x440/416/400/380 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$277
C1F002XES	240x120 VAC 60 Hz encapsulated transformer, 2kVA, 220/208/200/190x440/416/400/380 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$431
C1F003XES	240x120 VAC 60 Hz encapsulated transformer, 3kVA, 220/208/200/190x440/416/400/380 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$557
C1F005XES	240x120 VAC 60 Hz encapsulated transformer, 5kVA, 220/208/200/190x440/416/400/380 VAC primary, 240x120 VAC secondary, 1 phase, NEMA 3R shielded heavy duty enclosure, cULus 1604, T3C temperature classification	\$788