

	C-more Operator Interface Panels	Aust\$
EA7-S6M-R	6-inch C-more grayscale STN touch panel (5.7 inch viewable screen), 15 shades of gray, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (19.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), non-replaceable backlight, 50,000 hour half-life. *Base Model: Built-in USB, no Ethernet or Compact Flash support.	\$595
EA7-T6CL-R	Base model 6-inch C-more color TFT touch panel (5.7 inch viewable screen), 64K colors, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (20.4-28.8 VDC operating range), NEMA 4/4X, IP65 (when mounted correctly; for indoor use only), non-replaceable LED backlight, 50,000 hour half-life. Built-in USB, no Ethernet or Compact Flash support. This part is a direct replacement for the EA7-S6C-R part number	\$770
EA7-S6M	6-inch C-more grayscale STN touch panel (5.7 inch viewable screen), 15 shades of gray, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (19.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), non-replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$725
EA7-T6CL	6-inch C-more color TFT touch panel (5.7 inch viewable screen), 64K colors, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (20.4-28.8 VDC operating range), NEMA 4/4X, IP65 (when mounted correctly; for indoor use only), non-replaceable LED backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash. This part is a direct replacement for the EA7-S6C and EA7-T6C part numbers	\$995
EA7-T8C	8-inch C-more color TFT touch panel (8.4 inch viewable screen), 64K colors, 640 x 480 pixel VGA screen resolution, 400 MHz CPU, 24 VDC (18.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), user replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$1,495
EA7-T10C	10-inch C-more color TFT touch panel (10.4 inch viewable screen), 64K colors, 640 x 480 pixel VGA screen resolution, 400 MHz CPU, 24 VDC (18.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), user replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$2,290
EA7-T12C	12-inch C-more color TFT touch panel (12.1 inch viewable screen), 64K colors, 800 x 600 pixel SVGA screen resolution, 400 MHz CPU plus Graphic Accelerator chip, 24 VDC (18.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), user replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$2,790
EA7-T15C	15-inch C-more color TFT touch panel (15.0 inch viewable screen), 64K colors, 1024 x 768 XGA screen resolution, 400 MHz CPU plus Graphic Accelerator chip, 24V DC (20-30V operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), user replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$3,300

	C-more Operator Interface Panel Accessoires	Aust\$
EA-AC	AC/DC Adapter for C-more touch panels only; powered from a 100-240 VAC, 50/60 Hertz power source. Provides 24 VDC @ 1.5 A. Power Fault features help protect data being logged to Compact Flash during power failures. C-more panel must have firmware version 1.21 Build 6.18E or higher for proper operation.	\$99
EA-CF-CARD	512 MB high-speed industrial grade Compact Flash card for non-volatile storage. 85 degrees C maximum operating temperature makes it suitable for data logging in industrial applications. Recommended for C-more touch panels.	\$195
EA-CF-IF	Compact Flash Card Adapter Module, used when adding secondary Compact Flash option to Expansion Assembly. Compatible with EA-FLASH-128MB Compact Flash accessory.	\$79
EA-EXP-OPT	C-more I/O Module Expansion Assembly, used to hold secondary Compact Flash Adapter (EA-CF-IF) and future option modules	\$20
EA-6-ADPTR	6-inch mounting adapter plate, REQUIRED to mount a 6 inch C-more touch panel into enclosures with legacy thick-bezel EZTouch cutouts. Converts a 8.932 inch x 6.223 inch cutout to 7.522 inch x 5.625 inch cutout.	\$60
EA-6-COV2	6-inch non-glare protective overlay used to protect the 6-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$60
EA-8-COV2	8-inch non-glare protective overlay used to protect the 8-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$69
EA-10-COV2	10-inch non-glare protective overlay used to protect the 10-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$75
EA-12-COV2	12-inch non-glare protective overlay used to protect the 12-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$85
EA-15-COV2	15-inch non-glare protective overlay used to protect the 15-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$95
EA-6-GSK	6-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$36
EA-8-GSK	8-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$47
EA-10-GSK	10-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$55
EA-12-GSK	12-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$55
EA-15-GSK	15-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$83
EA-BRK-1	Spare panel mounting clips for 6-inch C-more touch panels. Package of 2 clips, includes 4 screws.	\$42
EA-BRK-2	Spare panel mounting clips for the 8-inch through 15-inch C-more touch panels. Package of 8 clips, includes 8 screws.	\$60
EA-6-BEZEL	Replacement NEMA 4/4X bezel for 6-inch C-more touch panel (ADC Repair Only)	\$75
EA-8-BEZEL	8-inch NEMA 4/4X bezel, customer replaceable, for C-more touch panel	\$148
EA-10-BEZEL	10-inch NEMA 4/4X bezel, customer replaceable, for C-more touch panel	\$172
EA-12-BEZEL	12-inch NEMA 4/4X bezel, customer replaceable, for C-more touch panel	\$148
EA-15-BEZEL	15-inch NEMA 4/4X bezel, customer replaceable, for C-more touch panel	\$278
EA-8-BULB	8-inch backlight assembly, customer replaceable, for 8-inch C-more touch panel, two bulbs per box Works with panel serial #'s EA7-T8C+10Z15B020 and earlier. Refer to C-more User Manual (EA-USER-M) for serial # formatting.	\$175
EA-10-BULB	10-inch backlight assembly, customer replaceable, for 10-inch C-more touch panel, two bulbs per box Works with panel serial #'s EA7-T10C+10Z11B080 and earlier. Refer to C-more User Manual (EA-USER-M) for serial # formatting	\$189
EA-12-BULB	12-inch backlight assembly, customer replaceable, for 12-inch C-more touch panel, one bulb per box Works with panel serial #'s EA7-T12C+10Z29B019 and earlier. Refer to C-more User Manual (EA-USER-M) for serial # formatting	\$125
EA-15-BULB	15-inch backlight assembly, customer replaceable, for 15-inch C-more touch panel, two bulbs per box Works with panel serial #'s EA7-T15C+10Z22B120 and earlier. Refer to C-more User Manual (EA-USER-M) for serial # formatting.	\$275
EA-DC-CON	Replacement 5-terminal DC power connector for C-more touch panel	\$34
EA-AC-CON	Replacement 3-terminal AC power connector for C-more touch panel AC adapter	\$18
EA-COMCON-3	DSUB 15-pin to 6-terminal RS422/485 PLC port adapter; plugs into the 15-pin serial port on the rear of the C-more panel to allow wire terminal connections for an RS-422/485 PLC communication cable	\$101
EA-ADPTR-4	DSUB 15-pin 90-degree PLC serial communications port adapter	\$94
EA-6-ADPTR-GSK	6-inch replacement NEMA 4/4X gasket for C-more touch panel adapter plate	\$55

	Pen Drive	Aust\$
SDCZ4-2048-A10	2GB SanDisk Cruzer micro pen drive. Compatible with Windows 98SE, ME, 2000, XP and Mac OS 9.1.x+, OS X 10.1.2+, Certified Windows XP and Mac OS X. Metal casing with lanyard and changeable colored skins and caps. Recommended for use with the C-more touch panels.	\$65
	<b>C-more Operator Interface Touch Panel Programming and Cables</b>	<b>Aust\$</b>
EA-PGMSW	C-more touch panel Windows-based configuration software. Requires Windows 2000 (Service Pack 4) or XP Home or Professional (Service Pack 2). Includes software installation guide and CD-ROM. Requires USB 1.1 or Ethernet connection to touch panel. Cables sold separately.	\$195
	<b>USB Cables</b>	<b>Aust\$</b>
USB-CBL-AB3	3-ft. (0.9 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$20
USB-CBL-AB6	6-ft. (1.8 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$20
USB-CBL-AB10	10-ft. (3 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$25
USB-CBL-AB15	15-ft. (4.6 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$29
	<b>C_more Communication cables</b>	<b>Aust\$</b>
EA-2CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a DL05, DL06, DL105, DL205, D3-350 or D4-450 CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to RJ12 modular connector.	\$39
EA-2CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a DL06, D2-250(-1) or D2-260 (bottom port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 15-pin male HD connector.	\$39
EA-3CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a D3-340 CPU top or bottom port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to RJ11 modular connector.	\$39
EA-4CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a DL405 (top port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 15-pin D-shell male connector.	\$39
EA-4CBL-2	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a D2-DCM, D3-350 (bottom port), a D3-232-DCU installed on a D3-330 or D3-340, or DL405 (bottom port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$39
EA-90-30-CBL	Shielded cable to connect any C-more touch panel to a GE Fanuc Series 90/30 or 90/70 serial port using SNPX protocol. 3m (9.8 ft) RS422A cable, 15-pin D-shell male connector to 15-pin D-shell male connector.	\$39
EA-SLC-232-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B SLC 5/03, 5/04 or 5/05 CPU with DF-1 port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 9-pin D-shell female connector.	\$39
EA-PLC5-232-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B PLC5 CPU with a DF1 port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$39
EA-MITSU-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a Mitsubishi FX Series CPU. 3m (9.8 ft) RS422C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$39
EA-MITSU-CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a Mitsubishi FX Series CPU. 3m (9.8 ft) RS422C cable, 15-pin D-shell male connector to 8-pin mini DIN connector.	\$39
EA-OMRON-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an Omron C200 or C500 CPU with HostLink protocol. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$39
EA-DH485-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B SLC500 CPU with a DH485 port, 3m (9.8 ft) cable	\$39
EA-MLOGIX-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B Micrologix 1000, 1200 or 1500 CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 8-pin DIN connector.	\$65
	<b>C-more Operator Interface Touch Panel Documentation</b>	
EA-USER-M	Manual contains hardware specifications and configuration information for C-more touch panel line	\$30

	C-more Micro-Graphic Operator Panels	Aust\$
EA1-S3ML	3.1-inch C-more Micro-Graphic Touch Panel with STN LCD monochrome, 128 x 64 dot display. Has 5 selectable screen colors: red, green, amber, lime, and yellow; 5 user-defined function keys with LED indicators. Power is supplied to the panel through the serial communication port connection when used with DirectLOGIC PLCs having an RJ12 communication port. EA-MG-SP1 (power supply with serial port option module) required when connecting to third party PLCs. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$275
EA1-S3ML-N	3.1-inch C-more Micro-Graphic Non-Touch Panel with STN LCD monochrome, 128 x 64 dot display. Has 5 selectable screen colors: red, green, amber, lime, and yellow; 5 user-defined function keys with LED indicators. Power is supplied to the panel through the serial communication port connection when used with DirectLOGIC PLCs having an RJ12 communication port. EA-MG-SP1 (power supply with serial port option module) required when connecting to third party PLCs. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$220
EA1-S3MLW	3.1-inch C-more Micro-Graphic Touch Panel with high-contrast white backlights. STN LCD monochrome, 128 x 64 dot display. Supports 5 selectable screen colors: white, pink1, pink2, pink3, and red; 5 user-defined function keys with LED indicators. Power is supplied to the panel through the serial communication port connection when used with DirectLOGIC PLCs having an RJ12 communication port. EA-MG-SP1 (power supply with serial port option module) required when connecting to third party PLCs. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$275
EA1-S3MLW-N	3.1-inch C-more Micro-Graphic Non-Touch Panel with high-contrast white backlights. STN LCD monochrome, 128 x 64 dot display. Supports 5 selectable screen colors: white, pink1, pink2, pink3, and red; 5 user-defined function keys with LED indicators. Power is supplied to the panel through the serial communication port connection when used with DirectLOGIC PLCs having an RJ12 communication port. EA-MG-SP1 (power supply with serial port option module) required when connecting to third party PLCs. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$220
EA1-T4CL	4-inch C-more (r) Micro-Graphic Touch Panel with TFT color LCD, 320 x 240 dot, 32,768 color display with LED backlight. Five user-defined function keys with LED indicators. Two built-in ports (USB Type-B port and 15-pin D-sub RS-232/422/485 port). Display supports Portrait and Landscape modes. NEMA 4/4X, IP65 (when mounted correctly; for indoor use only). Panel mount conforms to standard ¼ DIN cutout.	\$475
EA1-S6ML	6-inch C-more Micro-Graphic Touch Panel with STN LCD monochrome, 320 x 240 dot display. Has 5 selectable screen colors: red, green, amber, lime, and yellow; 5 user-defined function keys with LED indicators. Two built-in serial ports (RS-232 RJ12 port and 15-pin D-sub RS-232/422/485 port). Display supports Portrait and Landscape modes. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$450
EA1-S6MLW	6-inch C-more Micro-Graphic Touch Panel with STN LCD monochrome, 320 x 240 dot display. Supports 5 selectable screen colors: white, pink1, pink2, pink3, and red; 5 user-defined function keys with LED indicators. Two built-in serial ports (RS-232 RJ12 port and 15-pin D-sub RS-232/422/485 port). Display supports Portrait and Landscape modes. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$450
EA1-T6CL	6-inch C-more Micro-Graphic Touch Panel with TFT Color LCD, 320 x 240 dot, 32,768 color display with LED backlight. 5 user-defined function keys with LED indicators. Two built-in ports (USB Type-B port and 15-pin D sub RS-232/422/485 port). Display supports Portrait and Landscape modes. NEMA 4/4X, IP65 (when mounted correctly; for indoor use only).	\$590
EA1-MG-USER-M	Manual contains hardware and installation specifications for all C-More Micro-Graphic products.	\$30
EA1-TCL-M	Manual contains hardware and installation specifications for the 6-inch TFT, Color C-More Micro-Graphic panel (EA1-T6CL).	\$35
	C-more Micro-Graphic Keypad Bezel Options	Aust\$
EA-MG-BZ1	8-button keypad bezel for C-more Micro-Graphic panels, with 4 arrow adjust keys, and ESCAPE, MENU, CLEAR and ENTER buttons. Helps to reduce screen wear in heavy-duty applications where operators can use the keypad. Designed for easy drop-in of the Micro-Graphic panels.	\$85
EA-MG-BZ2	20-button keypad bezel with numeric keypad for C-more Micro-Graphic panels, 2 arrow adjust keys, and ESCAPE, MENU, CLEAR and ENTER buttons. Helps to reduce screen wear in heavy-duty applications where operators can use the keypad to enter numeric data. Designed for easy drop-in of the Micro-Graphic panels.	\$110
EA-MG6-BZ2	20-button keypad bezel with numeric keypad for 6-inch C-more Micro-Graphic panels being used in Landscape (horizontal) mounted mode, with 2 arrow adjust keys, and ESCAPE, MENU, CLEAR and ENTER buttons. Helps to reduce screen wear in heavy-duty applications where operators can use the keypad to enter numeric data. Designed for easy drop-in of the 6-inch Micro-Graphic panels.	\$140
EA-MG6-BZ2P	21-button keypad bezel with numeric keypad for 6-inch C-more Micro-Graphic panels being used in Portrait (vertical) mounted mode, with 2 arrow adjust keys, and ESCAPE, MENU, CLEAR and ENTER buttons. Helps to reduce screen wear in heavy-duty applications where operators can use the keypad to enter numeric data. Designed for easy drop-in of the 6-inch Micro-Graphic panels.	\$120

C-more Micro-Graphic, Bezels and Accessories		Aust\$
EA-MG6-S6ML-GSK	Replacement mounting gasket for 6-inch C-more Micro-Graphic panels. Package contains 1 gasket.	\$25
EA-MG6-BZ2-GSK	Replacement mounting gasket for 6-inch C-more Micro-Graphic bezels. Package contains 1 gasket.	\$45
EA-MG6-S6ML-FKL	Replacement function key label insert for 6-inch C-more Micro-Graphic panels. Package contains 5 labels: (3) blank label inserts, (1) portrait mode F1-F5 label insert, (1) landscape mode F1-F5 label insert.	\$35
EA1-MG6-USER-M	Manual contains hardware and installation specifications for 6-inch C-More Micro-Graphic panel products.	\$30
C-more Micro-Graphic Panel Programming Software and Cables		Aust\$
EA-MG-PGMSW	C-more Micro Graphic panel Windows-based configuration software. Requires Windows 2000 (Service Pack 4) or XP Home or Professional (Service Pack 2). Requires USB port connection from PC to touch panel. Includes CD-ROM. Programming cable (EA-MG-PGM-CBL) sold separately. Downloadable version available from the Web site at no charge. Software Help Files included in download.	\$35
EA-MG-PGM-CBL	6-ft. cable assembly to connect personal computer to any C-more Micro-Graphic panel for setup and programming. (Note: This cable assembly uses the PC's USB port and converts the signals to serial transmissions. The USB port supplies 5 VDC to the Micro-Graphic panel for configuration operations). Assembly includes standard USB A-type connector to B-type connector cable, custom converter, and an RS232C cable with RJ12 modular connector on each end.	\$60
C-more Micro-Graphic Options and Accessories		Aust\$
EA-MG-P1	Optional 24 VDC power adaptor for C-more Micro-Graphic 3-inch panels. Required when using third party PLCs, or when using 24 VDC power instead of the 5 VDC supplied from the RJ12 connector of a DirectLOGIC PLC . Panel supports Micro-Graphic expansion options.	\$49
EA-MG-SP1	Optional power adaptor with serial port option module for C-more Micro-Graphic 3-inch panels. 24 VDC power adaptor, with D-Sub 15-pin RS-232/RS-422/485 serial port. Required when using RS422, RS485 or third party PLCs. Panel supports Micro-Graphic expansion options. (This adapter only for use with C-more micro-graphic panels.)	\$85
EA-MG-S3ML-FKL	Replacement function key label insert for C-more Micro-Graphic panels. Labels are marked F1, F2, F3, F4, F5. Package contains 10 labels.	\$20
C-more Micro-Graphic panel brackets and gaskets		Aust\$
EA-MG-S3ML-BRK	Replacement mounting bracket for Micro-Graphic C-more panels. Package contains 2 brackets.	\$29
EA-MG-BZ1-BRK	Replacement mounting bracket for Micro-Graphic bezel EA-MG-BZ1. Package contains 2 brackets.	\$29
EA-MG-BZ2-BRK	Replacement mounting bracket for Micro-Graphic bezel EA-MG-BZ2. Package contains 6 brackets.	\$29
EA-MG-S3ML-GSK	Replacement mounting gasket for Micro-Graphic panels. Package contains 1 gasket.	\$29
EA-MG-BZ1-GSK	Replacement mounting gasket for Micro-Graphic bezel EA-MG-BZ1. Package contains 1 gasket.	\$29
EA-MG-BZ2-GSK	Replacement mounting gasket for Micro-Graphic bezel EA-MG-BZ2. Package contains 1 gasket.	\$29
EA-MG-COV-CL	Optional screen overlay used to protect C-more Micro-Graphic displays from minor scratches and wear. Package contains 5 screen overlays.	\$59
EA-MG-DC-CON	Replacement DC power connector terminal used on the EA-MG-P1 and EA-MG-SP1 power adaptors for Micro-Graphic panels. Package contains 5 connectors.	\$29
EA-4-COV2	4-inch non-glare protective overlay used to protect the 4-inch C-more (r) Micro-Graphic touch screen, helps reduce glare from external light sources, 3 overlays per package	\$50
EA-MG4-GSK	Replacement mounting gasket for EA1-T4CL C-more (r) Micro-Graphic panels. Package contains 1 gasket.	\$15
EA-MG4-FKL	Replacement function key label insert for 4-inch C-more (r) Micro-Graphic panels. Package contains 4 labels: (3) blank label inserts, (1) landscape mode F1-F5 label insert.	\$25