

	<b>C-more Operator Interface Panels</b>	<b>Aust\$</b>
EA7-S6M-R	6-inch C-more grayscale STN touch panel (5.7 inch viewable screen), 15 shades of gray, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (19.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), non-replaceable backlight, 50,000 hour half-life. *Base Model: Built-in USB, no Ethernet or Compact Flash support.	\$790
EA7-S6C-R	6-inch C-more color STN touch panel (5.7 inch viewable screen), 256 colors, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (19.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), non-replaceable backlight, 50,000 hour half-life. *Base Model: Built-in USB, no Ethernet or Compact Flash support.	\$1,180
EA7-S6M	6-inch C-more grayscale STN touch panel (5.7 inch viewable screen), 15 shades of gray, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (19.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), non-replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$925
EA7-S6C	6-inch C-more color STN touch panel (5.7 inch viewable screen), 256 colors, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (19.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), non-replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$1,290
EA7-T6C	6-inch C-more color TFT touch panel (5.7 inch viewable screen), 64K colors, 320 x 240 pixel QVGA screen resolution, 333 MHz CPU, 24 VDC (18.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), non-replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$1,490
EA7-T8C	8-inch C-more color TFT touch panel (8.4 inch viewable screen), 64K colors, 640 x 480 pixel VGA screen resolution, 400 MHz CPU, 24 VDC (18.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), user replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$1,890
EA7-T10C	10-inch C-more color TFT touch panel (10.4 inch viewable screen), 64K colors, 640 x 480 pixel VGA screen resolution, 400 MHz CPU, 24 VDC (18.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), user replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$2,970
EA7-T12C	12-inch C-more color TFT touch panel (12.1 inch viewable screen), 64K colors, 800 x 600 pixel SVGA screen resolution, 400 MHz CPU plus Graphic Accelerator chip, 24 VDC (18.2-28.8 VDC operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), user replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$3,520
EA7-T15C	15-inch C-more color TFT touch panel (15.0 inch viewable screen), 64K colors, 1024 x 768 XGA screen resolution, 400 MHz CPU plus Graphic Accelerator chip, 24V DC (20-30V operating range), NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only), user replaceable backlight, 50,000 hour half-life. Built-in Ethernet and USB; supports Compact Flash.	\$4,250

	<b>C-more Operator Interface Panel Accessoires</b>	<b>Aust\$</b>
EA-AC	AC/DC Adapter for C-more touch panels only; powered from a 100-240 VAC, 50/60 Hertz power source. Provides 24 VDC @ 1.5 A. Power Fault features help protect data being logged to Compact Flash during power failures. C-more panel must have firmware version 1.21 Build 6.18E or higher for proper operation.	\$130
EA-FLASH-128MB	128 MB high-speed industrial grade Compact Flash card for non-volatile storage. 85 degrees C maximum operating temperature makes it suitable for data logging in industrial applications. Recommended for C-more touch panels.	\$250
EA-CF-IF	Compact Flash Card Adapter Module, used when adding secondary Compact Flash option to Expansion Assembly. Compatible with EA-FLASH-128MB Compact Flash accessory.	\$95
EA-EXP-OPT	C-more I/O Module Expansion Assembly, used to hold secondary Compact Flash Adapter (EA-CF-IF) and future option modules	\$20
EA-6-ADPTR	6-inch mounting adapter plate, REQUIRED to mount a 6 inch C-more touch panel into enclosures with legacy thick-bezel EZTouch cutouts. Converts a 8.932 inch x 6.223 inch cutout to 7.522 inch x 5.625 inch cutout.	\$60
EA-6-COV1	6-inch replacement screen cover for the 6 inch C-more touch panel (qty 1). Screen covers not available for the 8 through 15 inch models.	TBA
EA-8-COV1	Replacement screen cover for the 8-inch C-more panel. Used for Internal ADC repair work only. Not sold to customers. (qty 1)	TBA
EA-10-COV1	Replacement screen cover for the 10-inch C-more panel. Used for Internal ADC repair work only. Not sold to customers. (qty 1)	TBA
EA-12-COV1	Replacement screen cover for the 12-inch C-more panel. Used for Internal ADC repair work only. Not sold to customers. (qty 1)	TBA
EA-15-COV1	Replacement screen cover for the 15-inch C-more panel. Used for Internal ADC repair work only. Not sold to customers. (qty 1)	TBA
EA-6-COV2	6-inch non-glare protective overlay used to protect the 6-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$65
EA-8-COV2	8-inch non-glare protective overlay used to protect the 8-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$70
EA-10-COV2	10-inch non-glare protective overlay used to protect the 10-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$95
EA-12-COV2	12-inch non-glare protective overlay used to protect the 12-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$95
EA-15-COV2	15-inch non-glare protective overlay used to protect the 15-inch C-more touch screen, helps reduce glare from external light sources, 3 overlays per package	\$120
EA-6-GSK	6-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$35
EA-8-GSK	8-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$40
EA-10-GSK	10-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$50
EA-12-GSK	12-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$45
EA-15-GSK	15-inch replacement NEMA 4/4X panel gasket for C-more touch panel	\$75
EA-BRK-1	Spare panel mounting clips for 6-inch C-more touch panels. Package of 2 clips, includes 4 screws.	\$36
EA-BRK-2	Spare panel mounting clips for the 8-inch through 15-inch C-more touch panels. Package of 8 clips, includes 8 screws.	\$45
EA-6-BEZEL	Replacement NEMA 4/4X bezel for 6-inch C-more touch panel (ADC Repair Only)	\$60
EA-8-BEZEL	8-inch NEMA 4/4X bezel, customer replaceable, for C-more touch panel	\$120
EA-10-BEZEL	10-inch NEMA 4/4X bezel, customer replaceable, for C-more touch panel	\$140
EA-12-BEZEL	12-inch NEMA 4/4X bezel, customer replaceable, for C-more touch panel	\$160
EA-15-BEZEL	15-inch NEMA 4/4X bezel, customer replaceable, for C-more touch panel	\$220
EA-8-BULB	8-inch backlight assembly, customer replaceable, for 8-inch C-more touch panel, two bulbs per box	\$195
EA-10-BULB	10-inch backlight assembly, customer replaceable, for 10-inch C-more touch panel, two bulbs per box	\$195
EA-12-BULB	12-inch backlight assembly, customer replaceable, for 12-inch C-more touch panel, one bulb per box	\$150
EA-15-BULB	15-inch backlight assembly, customer replaceable, for 15-inch C-more touch panel, two bulbs per box	\$295
EA-DC-CON	Replacement 5-terminal DC power connector for C-more touch panel	\$25
EA-AC-CON	Replacement 3-terminal AC power connector for C-more touch panel AC adapter	\$20
EA-COMCON-3	DSUB 15-pin to 6-terminal RS422/485 PLC port adapter; plugs into the 15-pin serial port on the rear of the C-more panel to allow wire terminal connections for an RS-422/485 PLC communication cable	\$75
EA-ADPTR-4	DSUB 15-pin 90-degree PLC serial communications port adapter	\$75
EA-6-ADPTR-GSK	6-inch replacement NEMA 4/4X gasket for C-more touch panel adapter plate	\$48

	<b>Pen Drive</b>	
SDCZ4-2048-A10	2GB SanDisk Cruzer micro pen drive. Compatible with Windows 98SE, ME, 2000, XP and Mac OS 9.1.x+, OS X 10.1.2+, Certified Windows XP and Mac OS X. Metal casing with lanyard and changeable colored skins and caps. Recommended for use with the C-more touch panels.	\$70
	<b>C-more Operator Interface Touch Panel Programming and Cables</b>	Aust\$
EA-PGMSW	C-more touch panel Windows-based configuration software. Requires Windows 2000 (Service Pack 4) or XP Home or Professional (Service Pack 2). Includes software installation guide and CD-ROM. Requires USB 1.1 or Ethernet connection to touch panel. Cables sold separately.	\$240
	<b>USB Cables</b>	
USB-CBL-AB3	3-ft. (0.9 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$25
USB-CBL-AB6	6-ft. (1.8 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$30
USB-CBL-AB10	10-ft. (3 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$35
USB-CBL-AB15	15-ft. (4.6 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$40
	<b>C_more Communication cables</b>	
EA-2CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a DL05, DL06, DL105, DL205, D3-350 or D4-450 CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to RJ12 modular connector.	\$59
EA-2CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a DL06, D2-250(-1) or D2-260 (bottom port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 15-pin male HD connector.	\$59
EA-3CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a D3-340 CPU top or bottom port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to RJ11 modular connector.	\$59
EA-4CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a DL405 (top port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 15-pin D-shell male connector.	\$59
EA-4CBL-2	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a D2-DCM, D3-350 (bottom port), a D3-232-DCU installed on a D3-330 or D3-340, or DL405 (bottom port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$59
EA-90-30-CBL	Shielded cable to connect any C-more touch panel to a GE Fanuc Series 90/30 or 90/70 serial port using SNPX protocol. 3m (9.8 ft) RS422A cable, 15-pin D-shell male connector to 15-pin D-shell male connector.	\$59
EA-SLC-232-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B SLC 5/03, 5/04 or 5/05 CPU with DF-1 port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 9-pin D-shell female connector.	\$59
EA-PLC5-232-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B PLC5 CPU with a DF1 port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$59
EA-MITSU-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a Mitsubishi FX Series CPU. 3m (9.8 ft) RS422C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$59
EA-MITSU-CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a Mitsubishi FX Series CPU. 3m (9.8 ft) RS422C cable, 15-pin D-shell male connector to 8-pin mini DIN connector.	\$59
EA-OMRON-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an Omron C200 or C500 CPU with HostLink protocol. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$59
EA-DH485-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B SLC500 CPU with a DH485 port, 3m (9.8 ft) cable	\$59
EA-MLOGIX-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B Micrologix 1000, 1200 or 1500 CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 8-pin DIN connector.	\$59
	<b>C-more Operator Interface Touch Panel Documentation</b>	
EA-USER-M	Manual contains hardware specifications and configuration information for C-more touch panel line	\$30

	<b>C-more Micro-Graphic Operator Panels</b>	<b>Aust\$</b>
EA1-S3ML	3.1-inch C-more Micro-Graphic Touch Panel with STN LCD monochrome, 128 x 64 dot display. Has 5 selectable screen colors: red, green, amber, lime, and yellow; 5 user-defined function keys with LED indicators. Power is supplied to the panel through the serial communication port connection when used with DirectLOGIC PLCs having an RJ12 communication port. EA-MG-SP1 (power supply with serial port option module) required when connecting to third party PLCs. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$350
EA1-S3ML-N	3.1-inch C-more Micro-Graphic Non-Touch Panel with STN LCD monochrome, 128 x 64 dot display. Has 5 selectable screen colors: red, green, amber, lime, and yellow; 5 user-defined function keys with LED indicators. Power is supplied to the panel through the serial communication port connection when used with DirectLOGIC PLCs having an RJ12 communication port. EA-MG-SP1 (power supply with serial port option module) required when connecting to third party PLCs. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$295
EA1-S3MLW	3.1-inch C-more Micro-Graphic Touch Panel with high-contrast white backlights. STN LCD monochrome, 128 x 64 dot display. Supports 5 selectable screen colors: white, pink1, pink2, pink3, and red; 5 user-defined function keys with LED indicators. Power is supplied to the panel through the serial communication port connection when used with DirectLOGIC PLCs having an RJ12 communication port. EA-MG-SP1 (power supply with serial port option module) required when connecting to third party PLCs. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$350
EA1-S3MLW-N	3.1-inch C-more Micro-Graphic Non-Touch Panel with high-contrast white backlights. STN LCD monochrome, 128 x 64 dot display. Supports 5 selectable screen colors: white, pink1, pink2, pink3, and red; 5 user-defined function keys with LED indicators. Power is supplied to the panel through the serial communication port connection when used with DirectLOGIC PLCs having an RJ12 communication port. EA-MG-SP1 (power supply with serial port option module) required when connecting to third party PLCs. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$270
EA1-MG-USER-M	Manual contains hardware and installation specifications for all C-More Micro-Graphic products.	\$30
	<b>C-more Micro-Graphic Keypad Bezel Options</b>	
EA-MG-BZ1	8-button keypad bezel for C-more Micro-Graphic panels, with 4 arrow adjust keys, and ESCAPE, MENU, CLEAR and ENTER buttons. Helps to reduce screen wear in heavy-duty applications where operators can use the keypad. Designed for easy drop-in of the Micro-Graphic panels.	\$110
EA-MG-BZ2	20-button keypad bezel with numeric keypad for C-more Micro-Graphic panels, 2 arrow adjust keys, and ESCAPE, MENU, CLEAR and ENTER buttons. Helps to reduce screen wear in heavy-duty applications where operators can use the keypad to enter numeric data. Designed for easy drop-in of the Micro-Graphic panels.	\$150
	<b>C-more Micro-Graphic Operator Panels, Bezels and Accessories</b>	<b>Aust\$</b>
EA1-S6ML	6-inch C-more Micro-Graphic Touch Panel with STN LCD monochrome, 320 x 240 dot display. Has 5 selectable screen colors: red, green, amber, lime, and yellow; 5 user-defined function keys with LED indicators. Two built-in serial ports (RS-232 RJ12 port and 15-pin D-sub RS-232/422/485 port). Display supports Portrait and Landscape modes. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$560
EA1-S6MLW	6-inch C-more Micro-Graphic Touch Panel with STN LCD monochrome, 320 x 240 dot display. Supports 5 selectable screen colors: white, pink1, pink2, pink3, and red; 5 user-defined function keys with LED indicators. Two built-in serial ports (RS-232 RJ12 port and 15-pin D-sub RS-232/422/485 port). Display supports Portrait and Landscape modes. NEMA 4/4X, IP-65 (when mounted correctly; for indoor use only).	\$560
EA-MG6-BZ2	20-button keypad bezel with numeric keypad for 6-inch C-more Micro-Graphic panels being used in Landscape (horizontal) mounted mode, with 2 arrow adjust keys, and ESCAPE, MENU, CLEAR and ENTER buttons. Helps to reduce screen wear in heavy-duty applications where operators can use the keypad to enter numeric data. Designed for easy drop-in of the 6-inch Micro-Graphic panels.	\$185
EA-MG6-BZ2P	21-button keypad bezel with numeric keypad for 6-inch C-more Micro-Graphic panels being used in Portrait (vertical) mounted mode, with 2 arrow adjust keys, and ESCAPE, MENU, CLEAR and ENTER buttons. Helps to reduce screen wear in heavy-duty applications where operators can use the keypad to enter numeric data. Designed for easy drop-in of the 6-inch Micro-Graphic panels.	\$185
EA-MG6-S6ML-GSK	Replacement mounting gasket for 6-inch C-more Micro-Graphic panels. Package contains 1 gasket.	\$20
EA-MG6-BZ2-GSK	Replacement mounting gasket for 6-inch C-more Micro-Graphic bezels. Package contains 1 gasket.	\$40
EA-MG6-S6ML-FKL	Replacement function key label insert for 6-inch C-more Micro-Graphic panels. Package contains 5 labels: (3) blank label inserts, (1) portrait mode F1-F5 label insert, (1) landscape mode F1-F5 label insert.	\$30
EA1-MG6-USER-M	Manual contains hardware and installation specifications for 6-inch C-More Micro-Graphic panel products.	\$30

<b>C-more Micro-Graphic Panel Programming Software and Cables</b>		
EA-MG-PGMSW	C-more Micro Graphic panel Windows-based configuration software. Requires Windows 2000 (Service Pack 4) or XP Home or Professional (Service Pack 2). Requires USB port connection from PC to touch panel. Includes CD-ROM. Programming cable (EA-MG-PGM-CBL) sold separately. Downloadable version available from the Web site at no charge. Software Help Files included in download.	\$50
EA-MG-PGM-CBL	6-ft. cable assembly to connect personal computer to any C-more Micro-Graphic panel for setup and programming. (Note: This cable assembly uses the PC's USB port and converts the signals to serial transmissions. The USB port supplies 5 VDC to the Micro-Graphic panel for configuration operations). Assembly includes standard USB A-type connector to B-type connector cable, custom converter, and an RS232C cable with RJ12 modular connector on each end.	\$75
<b>C-more Micro-Graphic Options and Accessories</b>		
EA-MG-P1	Optional 24 VDC power adaptor for C-more Micro-Graphic 3-inch panels. Required when using third party PLCs, or when using 24 VDC power instead of the 5 VDC supplied from the RJ12 connector of a DirectLOGIC PLC. Panel supports Micro-Graphic expansion options.	\$60
EA-MG-SP1	Optional power adaptor with serial port option module for C-more Micro-Graphic 3-inch panels. 24 VDC power adaptor, with D-Sub 15-pin RS-232/RS-422/485 serial port. Required when using RS422, RS485 or third party PLCs. Panel supports Micro-Graphic expansion options. (This adapter only for use with C-more micro-graphic panels.)	\$95
EA-MG-S3ML-FKL	Replacement function key label insert for C-more Micro-Graphic panels. Labels are marked F1, F2, F3, F4, F5. Package contains 10 labels.	\$30
<b>C-more Micro-Graphic panel brackets and gaskets</b>		
EA-MG-S3ML-BRK	Replacement mounting bracket for Micro-Graphic C-more panels. Package contains 2 brackets.	\$39
EA-MG-BZ1-BRK	Replacement mounting bracket for Micro-Graphic bezel EA-MG-BZ1. Package contains 2 brackets.	\$39
EA-MG-BZ2-BRK	Replacement mounting bracket for Micro-Graphic bezel EA-MG-BZ2. Package contains 6 brackets.	\$39
EA-MG-S3ML-GSK	Replacement mounting gasket for Micro-Graphic panels. Package contains 1 gasket.	\$30
EA-MG-BZ1-GSK	Replacement mounting gasket for Micro-Graphic bezel EA-MG-BZ1. Package contains 1 gasket.	\$35
EA-MG-BZ2-GSK	Replacement mounting gasket for Micro-Graphic bezel EA-MG-BZ2. Package contains 1 gasket.	\$35
EA-MG-COV-CL	Optional screen overlay used to protect C-more Micro-Graphic displays from minor scratches and wear. Package contains 5 screen overlays.	\$75
EA-MG-DC-CON	Replacement DC power connector terminal used on the EA-MG-P1 and EA-MG-SP1 power adaptors for Micro-Graphic panels. Package contains 5 connectors.	\$30
<b>DV-1000, Cables, and Accessories</b>		
DV-1000	DirectVIEW 1000 Timer/Counter access unit for DL05, DL06, DL105, DL205, DL350, and DL405 CPUs. Can be used to change preset values, display discrete bit ranges, display user defined messages, and display system error messages. Cable not included! See cables below.	\$390
D-24VIEW-M	DV-1000 User Manual. Includes sample setup programs on diskette.	\$40
DV-1000CBL	Shielded cable to connect C-more Micro-Graphic and DV-1000 panels to the DL05, DL06, DL105, DL230, DL240, DL250, DL350 or DL450 CPU phone jacks. 2m (6.56 ft.) RS232C cable has an RJ12 modular connector on each end. (FA-15HD required if going to 15-pin HD port.)	\$40
D4-1000CBL	Shielded cable to connect C-more Micro-Graphic and DV-1000 panels to 15-pin port on any DL405 CPU. 2m (6.56 ft.) RS232C cable, RJ12 modular connector to 15-pin D-shell male connector.	\$48
DV-1000KPD	Replacement keypad for DV-1000 (quantity 2)	\$80