

Speed Code		Proximity Sensors IP69K for harsh duty / food and beverage applications	Aust\$
Q701	PFM1-AP-3H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 4mm nominal sensing distance, normally open output, 800Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$59
Q702	PFM1-AP-4H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, unshielded, 7mm nominal sensing distance, normally open output, 800Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$59
Q703	PFM1-BN-1H	Proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, shielded, 2mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q704	PFM1-BP-1H	Proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, shielded, 2mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q705	PFM1-BN-2H	Proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, unshielded, 4mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q706	PFM1-BP-2H	Proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, unshielded, 4mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q707	PFM1-BN-3H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, shielded, 4mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q708	PFM1-BP-3H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, shielded, 4mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q709	PFM1-BN-4H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, unshielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q710	PFM1-BP-4H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, unshielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q715	PFK1-AP-3H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 8mm nominal sensing distance, normally open output, 600Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$59
Q716	PFK1-AP-4H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, unshielded, 12mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$59
Q717	PFK1-BN-1H	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, shielded, 5mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$79
Q718	PFK1-BP-1H	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, shielded, 5mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$79
Q719	PFK1-BN-2H	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, unshielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$79
Q720	PFK1-BP-2H	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, unshielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$79
Q721	PFK1-BN-3H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, shielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$79

Q722	PFK1-BP-3H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, shielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$79
Q723	PFK1-BN-4H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, unshielded, 12mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$89
Q724	PFK1-BP-4H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, unshielded, 12mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$89
Q730	VFK1-A0-1M	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 20-140 VAC/VDC, 2-wire, PNP, shielded, 5mm nominal sensing distance, normally open output, 25Hz (AC) / 400Hz (DC) switching frequency, 1/2 inch micro AC quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$89
Q731	VFK1-A0-2M	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 20-140 VAC/VDC, 2-wire, PNP, unshielded, 12mm nominal sensing distance, normally open output, 25Hz (AC) / 300Hz (DC) switching frequency, 1/2 inch micro AC quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$89
Q735	PFT1-AP-3H	Proximity sensor, 30mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel short housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 14mm nominal sensing distance, normally open output, 50Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$75
Q736	PFT1-AP-4H	Proximity sensor, 30mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel short housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, unshielded, 22mm nominal sensing distance, normally open output, 100Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$75
Q737	PFT2-AP-3H	Proximity sensor, 30mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 15mm nominal sensing distance, normally open output, 50Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$75
Q738	PFT2-AP-4H	Proximity sensor, 30mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, unshielded, 22mm nominal sensing distance, normally open output, 100Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$75
Q741	VFT1-A0-1M	Proximity sensor, 30mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 20-140 VAC/VDC, 2-wire, PNP, shielded, 14mm nominal sensing distance, normally open output, 25Hz (AC) / 100Hz (DC) switching frequency, 1/2 inch micro AC quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$95
Q742	VFT1-A0-2M	Proximity sensor, 30mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 20-140 VAC/VDC, 2-wire, PNP, unshielded, 22mm nominal sensing distance, normally open output, 25Hz (AC) / 100Hz (DC) switching frequency, 1/2 inch micro AC quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$95
Q745	MAFM1-A0-1H	Magnetic proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 60mm nominal sensing distance, normally open output, 5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$69
Q746	MAFK1-A0-1H	Magnetic proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 70mm nominal sensing distance, normally open output, 5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$79
Q747	AW-MAG	Damping magnet, Barium ferrite with 316L stainless steel coating, use with MAFM1 and MAFK1 series sensors	\$59

		New Quick-Disconnect Sensors	Aust\$
Q831	EVT221	M12 cable for quick-disconnect sensors, 12mm axial female, IP69K rated, stainless steel plug, 4-pole, 5-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$20
Q832	EVT222	M12 cable for quick-disconnect sensors, 12mm right angle female, IP69K rated, stainless steel plug, 4-pole, 5-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q833	EVT223	M12 cable for quick-disconnect sensors, 12mm axial female, IP69K rated, stainless steel plug, 4-pole, 10-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$20
Q834	EVT224	M12 cable for quick-disconnect sensors, 12mm right angle female, IP69K rated, stainless steel plug, 4-pole, 10-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q835	EVT225	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 0.3-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q836	EVT226	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 0.3-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q837	EVT227	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 0.6-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q838	EVT228	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 0.6-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$32
Q839	EVT229	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 1-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$35
Q840	EVT230	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 1-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q841	EVT231	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 2-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q842	EVT232	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 2-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q843	EVT233	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 5-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$29
Q844	EVT234	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 5-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$35
		New Quick-Disconnect Sensors Accessories	Aust\$
Q845	E18446	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch axial female, IP69K rated, stainless steel plug, 3-pole, 5-meter cable, yellow PVC outer jacket suitable for food and beverage applications	\$35
Q846	E18447	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch right angle female, IP69K rated, stainless steel plug, 3-pole, 5-meter cable, yellow PVC outer jacket suitable for food and beverage applications	\$45
Q847	E18448	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch axial female, IP69K rated, stainless steel plug, 3-pole, 10-meter cable, yellow PVC outer jacket suitable for food and beverage applications	\$39
Q848	E18449	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch right angle female, IP69K rated, stainless steel plug, 3-pole, 10-meter cable, yellow PVC outer jacket suitable for food and beverage applications	\$45