

| 1/16 DIN Temperature/Process Controllers | | Aust\$ |
|---|--|---------------|
| SL4848-VR | SOLO (tm) dual-output process controller, 1/16 DIN, with one 11-15 VDC pulse output (40mA max), and one 5A SPST mechanical relay output (or can be used as an alarm) and two 3A SPST alarm relays (with a shared common). Universal inputs include T/C, RTD and analog (0-5V, 0-10V, 0-20mA, 4-20mA, 0-50mV), accepts 100-240 VAC operational power. PID, ON/OFF and manual control plus 64-segment Ramp/Soak profile, standard RS-485 communications (Modbus ASCII and RTU). Mounting clips are included. | \$257 |
| SL4848-CR | SOLO (tm) dual-output process controller, 1/16 DIN, with one 4-20mA analog output, one 5A SPST mechanical relay output (or can be used as an alarm) and two 3A SPST alarm relays (with a shared common). Universal inputs include T/C, RTD and analog (0-5V, 0-10V, 0-20mA, 4-20mA, 0-50mV), accepts 100-240 VAC operational power. PID, ON/OFF and manual control plus 64-segment Ramp/Soak profile, standard RS-485 communications (Modbus ASCII and RTU). Mounting clips are included. | \$257 |
| SL4848-LR | SOLO (tm) dual-output process controller, 1/16 DIN, with one 0-5V or 0-10V analog output, one 5A SPST mechanical relay output (or can be used as an alarm) and two 3A SPST alarm relays (with a shared common). Universal inputs include T/C, RTD and analog (0-5V, 0-10V, 0-20mA, 4-20mA, 0-50mV), accepts 100-240 VAC operational power. PID, ON/OFF and manual control plus 64-segment Ramp/Soak profile, standard RS-485 communications (Modbus ASCII and RTU). Mounting clips are included. | \$257 |
| SL4848-VV | SOLO (tm) dual-output process controller, 1/16 DIN, with two 11-15 VDC pulse outputs (40mA max), and two 3A SPST alarm relays (with a shared common). Universal inputs include T/C, RTD and analog (0-5V, 0-10V, 0-20mA, 4-20mA, 0-50mV), accepts 100-240 VAC operational power. PID, ON/OFF and manual control plus 64-segment Ramp/Soak profile, standard RS-485 communications (Modbus ASCII and RTU). Mounting clips are included. | \$257 |
| Temperature/Process Controller Spare Parts and Accessories | | |
| SL-CLP-1 | Mounting clips for 1/32 DIN process controllers, 8 clips per package | \$31 |
| SL-CLP-2 | Mounting clips for 1/16, 1/8 and 1/4 DIN process controllers, 20 clips per package | \$23 |
| SL-SOFT | Optional configuration and monitoring software for SOLO (tm) process controllers, with available 8-pen trend graph (available only as a download from AutomationDirect Web site) | Free |
| SL-USER-M | SOLO (tm) software user manual, available as a download from AutomationDirect Web site | Free |

| Q Series Electromechanical Cube Relays and Accessories | | Aust\$ |
|---|---|---------------|
| QL2N1-A120 | Cube relay, 120 VAC coil, 2PDT, 10A contact rating, with LED indicator | \$27 |
| QL2N1-D24 | Cube relay, 24 VDC coil, 2PDT, 10A contact rating, with LED indicator | \$27 |
| QL2X1-D24 | Cube relay, 24 VDC coil, 2PDT, 10A contact rating, with LED indicator and diode protection | \$31 |
| QL2N1-A220 | Cube relay, 240 VAC coil, 2PDT, 10A contact rating, with LED indicator | \$27 |
| QL4N1-A120 | Cube relay, 120 VAC coil, 4PDT, 10A contact rating, with LED indicator | \$31 |
| QL4N1-D24 | Cube relay, 24 VDC coil, 4PDT, 10A contact rating, with LED indicator | \$28 |
| QL4X1-D24 | Cube relay, 24 VDC coil, 4PDT, 10A contact rating, with LED indicator and diode protection | \$41 |
| QL4N1-A220 | Cube relay, 240 VAC coil, 4PDT, 10A contact rating, with LED indicator | \$31 |
| QM2N1-A120 | Cube relay, 120 VAC coil, 2PDT, 5A contact rating, with LED indicator | \$13 |
| QM2N1-D24 | Cube relay, 24 VDC coil, 2PDT, 5A contact rating, with LED indicator | \$13 |
| QM2X1-D24 | Cube relay, 24 VDC coil, 2PDT, 5A contact rating, with LED indicator and diode protection | \$25 |
| QM2N1-A220 | Cube relay, 240 VAC coil, 2PDT, 5A contact rating, with LED indicator | \$13 |
| QM4N1-A120 | Cube relay, 120 VAC coil, 4PDT, 3A contact rating, with LED indicator | \$13 |
| QM4N1-D24 | Cube relay, 24 VDC coil, 4PDT, 3A contact rating, with LED indicator | \$13 |
| QM4X1-D24 | Cube relay, 24 VDC coil, 4PDT, 3A contact rating, with LED indicator and diode protection | \$25 |
| QM4N1-A220 | Cube relay, 240 VAC coil, 4PDT, 3A contact rating, with LED indicator | \$22 |
| SQL08D | DIN rail socket for QL2 series relays | \$9 |
| SQL14D | DIN rail socket for QL4 series relays | \$9 |
| SQM08D | DIN rail socket for QM2 series relays | \$9 |
| SQM14D | DIN rail socket for QM4 series relays | \$9 |
| 78RELAYnotes | 78 Series Electromechanical Cube Relays and Accessories | |
| 781-1C-24D | Cube relay, 24 VDC coil voltage, 1PDT, 15A contact rating, with LED indicator and push-to-test button | \$10 |
| 781-1C-24A | Cube relay, 24 VAC coil voltage, 1PDT, 15A contact rating, with LED indicator and push-to-test button | \$12 |
| 781-1C-120A | Cube relay, 120 VAC coil voltage, 1PDT, 15A contact rating, with LED indicator and push-to-test button | \$12 |
| 781-1C-240A | Cube relay, 240 VAC coil voltage, 1PDT, 12A contact rating, with LED indicator and push-to-test button | \$14 |
| 782-2C-24D | Cube relay, 24 VDC coil voltage, 2PDT, 15A contact rating, with LED indicator and push-to-test button | \$15 |
| 782-2C-24A | Cube relay, 24 VAC coil voltage, 2PDT, 15A contact rating, with LED indicator and push-to-test button | \$15 |
| 782-2C-120A | Cube relay, 120 VAC coil voltage, 2PDT, 15A contact rating, with LED indicator and push-to-test button | \$15 |
| 782-2C-240A | Cube relay, 240 VAC coil voltage, 2PDT, 15A contact rating, with LED indicator and push-to-test button | \$17 |
| 783-3C-24D | Cube relay, 24 VDC coil voltage, 3PDT, 15A contact rating, with LED indicator and push-to-test button | \$21 |
| 783-3C-24A | Cube relay, 24 VAC coil voltage, 3PDT, 15A contact rating, with LED indicator and push-to-test button | \$21 |
| 783-3C-120A | Cube relay, 120 VAC coil voltage, 3PDT, 15A contact rating, with LED indicator and push-to-test button | \$21 |
| 783-3C-240A | Cube relay, 240 VAC coil voltage, 3PDT, 12A contact rating, with LED indicator and push-to-test button | \$21 |
| 784-4C-24D | Cube relay, 24 VDC coil voltage, 4PDT, 15A contact rating, with LED indicator and push-to-test button | \$20 |
| 784-4C-24A | Cube relay, 24 VAC coil voltage, 4PDT, 15A contact rating, with LED indicator and push-to-test button | \$20 |
| 784-4C-120A | Cube relay, 120 VAC coil voltage, 4PDT, 15A contact rating, with LED indicator and push-to-test button | \$20 |
| 784-4C-240A | Cube relay, 240 VAC coil voltage, 4PDT, 12A contact rating, with LED indicator and push-to-test button | \$20 |
| 781-1C-SKT | DIN-rail socket for 781 series cube relays | \$10 |
| 782-2C-SKT | DIN-rail socket for 782 and AD-70S2 series cube relays | \$10 |
| 783-3C-SKT | DIN-rail socket for 783 series cube relays | \$12 |
| 784-4C-SKT-1 | DIN-rail socket for 784 series cube relays | \$10 |
| AD-70-STM-1 | Socket timing module for 783 and 784 series relays. Includes 8 dipswitch selectable time scales from 0.1 second to 10 days. Rotary potentiometer timing adjustment, 24-240 VAC/VDC relay compatible, green LED indicator. | \$85 |

| 75 Series Electromechanical Octal Relays and Accessories | | |
|---|--|-------|
| 750-2C-24D | Octal relay, 24 VDC coil voltage, 2PDT, 12A contact rating, with LED indicator and push-to-test button | \$21 |
| 750-2C-24A | Octal relay, 24 VAC coil voltage, 2PDT, 12A contact rating, with LED indicator and push-to-test button | \$21 |
| 750-2C-120A | Octal relay, 120 VAC coil voltage, 2PDT, 12A contact rating, with LED indicator and push-to-test button | \$21 |
| 750-2C-240A | Octal relay, 240 VAC coil voltage, 2PDT, 12A contact rating, with LED indicator and push-to-test button | \$22 |
| 750-3C-24D | Octal relay, 24 VDC coil voltage, 3PDT, 12A contact rating, with LED indicator and push-to-test button | \$24 |
| 750-3C-24A | Octal relay, 24 VAC coil voltage, 3PDT, 12A contact rating, with LED indicator and push-to-test button | \$25 |
| 750-3C-120A | Octal relay, 120 VAC coil voltage, 3PDT, 12A contact rating, with LED indicator and push-to-test button | \$25 |
| 750-3C-240A | Octal relay, 240 VAC coil voltage, 3PDT, 12A contact rating, with LED indicator and push-to-test button | \$26 |
| 755-2C-120A | Magnetic latching relay, single coil, 120 VAC coil voltage, 16A contact rating, 11 pin octal pin configuration (750-3C-SKT base sold separately) | \$25 |
| 755-2C-240A | Magnetic latching relay, single coil, 240 VAC coil voltage, 16A contact rating, 11 pin octal pin configuration (750-3C-SKT base sold separately) | \$28 |
| 755-2CD-24D | Magnetic latching relay, dual coil, 24 VDC coil voltage, 16A contact rating, 11 pin octal configuration (750-3C-SKT base sold separately) | \$24 |
| 750-2C-SKT | DIN-rail socket for 750-2C series octal relays, 8-pin configuration | \$11 |
| 750-3C-SKT | DIN-rail socket for 750-3C and 755 series octal relays, 11-pin configuration | \$12 |
| 33-796-1 | Bus bar used to connect multiple octal relays in parallel. Package includes 5 pair of bus bars to connect up to 5 relays together. | \$8 |
| 78 and 75 Series Electromechanical Relay Accessories | | |
| AD-ASMD-250 | Protection diode module for 784 and 750 series relays. Package includes 5 modules. | \$26 |
| AD-BSMD-250 | Protection diode module for 782 series relays. Package includes 5 modules. | \$21 |
| AD-ASMM-24 | MOV module for 784 and 750 series relays that operate at 24 VAC coil voltage. Package includes 5 modules. | \$21 |
| AD-ASMM-120 | MOV module for 784 and 750 series relays that operate at 120 VAC coil voltage. Package includes 5 modules. | \$21 |
| AD-ASMM-240 | MOV module for 784 and 750 series relays that operate at 240 VAC coil voltage. Package includes 5 modules. | \$21 |
| AD-BSMM-24 | MOV module for 782 series relays that operate at 24 VAC coil voltage. Package includes 5 modules. | \$21 |
| AD-BSMM-120 | MOV module for 782 series relays that operate at 120 VAC coil voltage. Package includes 5 modules. | \$21 |
| AD-BSMM-240 | MOV module for 782 series relays that operate at 240 VAC coil voltage. Package includes 5 modules. | \$21 |
| Electromechanical Card Relays and Accessories | | |
| RS4N-DE | Card relay (4 included), mounted in socket, 24 VDC coil, SPST, 5A contact rating. TY3 relay remover included. | \$72 |
| RS6N-DE | Card relay (6 included), mounted in socket, 24 VDC coil, SPST, 5A contact rating. TY3 relay remover included. | \$94 |
| RB105-DE | Spare relays for the RS series relays, 24 VDC coil, SPST, 5A contact rating, package of 10 | \$66 |
| RZ4N | Terminal guard for RS series relays, package of 10 | \$39 |
| TY3 | Relay remover for RS series relays, package of 10 | \$19 |
| Solid State Relays | | |
| AD-SSR210-AC | Solid state DIN-rail mount relay, 90-280 VAC coil voltage, 24-280 VAC load voltage, 10A contact rating. Finger-safe design and LED status lamp. | \$101 |
| AD-SSR225-AC | Solid state DIN-rail mount relay, 90-280 VAC coil voltage, 24-280 VAC load voltage, 25A contact rating. Finger-safe design and LED status lamp. | \$118 |
| AD-SSR210-DC | Solid state DIN-rail mount relay, 3-32 VDC coil voltage, 24-280 VAC load voltage, 10A contact rating. Finger-safe design and LED status lamp. | \$81 |
| AD-SSR225-DC | Solid state DIN-rail mount relay, 3-32 VDC coil voltage, 24-280 VAC load voltage, 25A contact rating. Finger-safe design and LED status lamp. | \$113 |
| AD-70S2-04B | Solid state plug-in relay, 3-30 VDC coil voltage, 24-140 VAC load voltage, 4A contact rating | \$49 |
| AD-70S2-04C | Solid state plug-in relay, 3-30 VDC coil voltage, 24-280 VAC load voltage, 4A contact rating | \$49 |
| AD-70S2-04D | Solid state plug-in relay, 3-30 VDC coil voltage, 8-50 VAC load voltage, 4A contact rating | \$49 |

| FUJI Timer Relays and Accessories | | |
|-----------------------------------|---|-------|
| MS4SM-AP-ADC | Multi-mode timer with selectable timing range from 0.05 seconds to 60 hours, 100-240 VAC input power, DPDT relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately. | \$109 |
| MS4SA-AP-ADC | On-delay timer with selectable timing range from 0.05 seconds to 60 hours, 100-240 VAC input power, DPDT relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately. | \$109 |
| MS4SC-AP-ADC | On-delay timer with selectable timing range from 0.05 seconds to 60 hours, 100-240 VAC input power. SPDT timed relay output and SPDT instant relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately. | \$109 |
| MS4SM-CE-ADC | Multi-mode timer with selectable timing range from 0.05 seconds to 60 hours, 24 VDC/VAC input power, DPDT relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately. | \$109 |
| MS4SA-CE-ADC | On-delay timer with selectable timing range from 0.05 seconds to 60 hours, 24 VDC/VAC input power, DPDT relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately. | \$109 |
| MS4SC-CE-ADC | On-delay timer with selectable timing range from 0.05 seconds to 60 hours, 24 VDC/VAC input power, SPDT timed relay output and SPDT instant relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately. | \$101 |
| ST7P-2DE5S-ADC | Mini-DIN on-delay timer with timing range of 0.4 seconds to 5 seconds, 24 VDC input power, DPDT relay output | \$83 |
| ST7P-2DE3T-ADC | Mini-DIN on-delay timer with timing range of 2 seconds to 30 seconds, 24 VDC input power, DPDT relay output | \$83 |
| ST7P-2DE6T-ADC | Mini-DIN on-delay timer with timing range of 4 seconds to 60 seconds, 24 VDC input power, DPDT relay output | \$83 |
| ST7P-2DE1N-ADC | Mini-DIN on-delay timer with timing range of 1 min. to 10 min., 24 VDC input power, DPDT relay output | \$81 |
| ST7P-2DE6N-ADC | Mini-DIN on-delay timer with timing range of 4 min. to 60 min., 24 VDC input power, DPDT relay output | \$81 |
| TP411X | DIN rail mounting socket for MS4SM series timers | \$16 |
| TP48X | DIN rail mounting socket for MS4SA and MS4SC series timers | \$16 |
| TP88X2 | DIN rail mounting socket for ST7P series timers | \$16 |
| TP411SBA | Panel mounting socket for MS4SM series timers | \$16 |
| TP48SB | Mounting clips for 1/16th DIN timers and temperature/process controllers, 5 clips per package | \$16 |
| PANEL-16 | Mounting clips for 1/16th DIN timers and temperature/process controllers, 5 clips per package | \$16 |