

	Safety Products	Aust\$
	Safety Relays	Aust\$
LG5924-02-61-24	Safety relay module, single channel operation for emergency stop circuits, 24 VDC coil voltage, 2 N.O. positive guided safety contacts, manual or automatic restart	\$135
LG5924-48-61-24	Safety relay module, single channel operation for emergency stop circuits, 24 VDC coil voltage, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact, manual or automatic restart	\$149
LG5924-48-61-110	Safety relay module, single channel operation for emergency stop circuits, 110 VAC 50/60 Hz coil voltage, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact, manual or automatic restart	\$169
LG5924-48-61-230	Safety relay module, single channel operation for emergency stop circuits, 230 VAC 50/60 Hz coil voltage, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact, manual or automatic restart	\$169
LG5925-48-61-24	Safety relay module, dual channel operation for emergency stop and gate safety circuits, 24 VAC/DC coil voltage, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact, manual or automatic restart	\$169
LG5925-48-61-110	Safety relay module, dual channel operation for emergency stop and gate safety circuits, 110 VAC 50/60 Hz coil voltage, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact, manual or automatic restart	\$189
LG5925-48-61-230	Safety relay module, dual channel operation for emergency stop and gate safety circuits, 230 VAC 50/60 Hz coil voltage, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact, manual or automatic restart	\$189
BH5928-92-61-24-1	Safety relay module, timed, dual channel operation for emergency stop and gate safety circuits, 24 VAC/DC coil voltage, 3 N.O. time delay (0.1 to 1 second) positive guided safety contacts, 2 N.O. instantaneous positive guided safety contacts and 1 N.C. instantaneous monitoring contact, manual or automatic restart	\$299
BH5928-92-61-24-5	Safety relay module, timed, dual channel operation for emergency stop and gate safety circuits, 24 VAC/DC coil voltage, 3 N.O. time delay (0.5 to 5 second) positive guided safety contacts, 2 N.O. instantaneous positive guided safety contacts and 1 N.C. instantaneous monitoring contact, manual or automatic restart	\$299
BH5928-92-61-24-30	Safety relay module, timed, dual channel operation for emergency stop and gate safety circuits, 24 VAC/DC coil voltage, 3 N.O. time delay (3 to 30) second positive guided safety contacts, 2 N.O. instantaneous positive guided safety contacts and 1 N.C. instantaneous monitoring contact, manual or automatic restart	\$299
LG5929-60-100-61	Safety relay module extension module, 24 VAC/DC coil, 5 N.O. positive guided safety contacts and 1 N.C. monitoring contact	\$145
BG5933-22-61-24	Safety relay module, two-hand control, 24 VDC coil, 2 N.O. positive guided safety contacts and 1 N.C. monitoring contact	\$210
BH5933-48-61-110	Safety relay module, two-hand control, 110 VAC 50/60 Hz coil, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact	\$289
BH5933-48-61-230	Safety relay module, two-hand control, 230 VAC 50/60 Hz coil, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact	\$289
LG5925-48-900-61	Safety relay module, light curtain controller with dual channel operation, 24 VDC coil, 3 N.O. positive guided safety contacts and 1 N.C. monitoring contact, manual or automatic restart	\$175
BH5902-22-01MF2-61	Safety relay module, light curtain controller with dual channel operation and selectable modes (standard, muting, stepping), 24 VDC coil, 2 N.O. positive guided safety contacts and 1 N.C. monitoring contact, manual or automatic restart	\$495

	Safety Switches	Aust\$
SP2K20X11	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$23
SP2K20W02	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$23
SP2K120X11	Safety switch, tongue (key) interlock operated, 360 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$28
SP2K120W02	Safety switch, tongue (key) interlock operated, 360 degree adjustable head, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$28
SDM2K20X11	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$29
SDM2K20W02	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 2 N.C. contacts with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$29
SDM2K120X11	Safety switch, tongue (key) interlock operated, 360 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$33
SDM2K120W02	Safety switch, tongue (key) interlock operated, 360 degree adjustable head, 2 N.C. contacts with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$33
SBM2K40X11	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$39
SBM2K40W02	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 2 N.C. contacts with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$39
SBM2K40X12	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 1 N.O. and 2 N.C. contact with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$42
SBM2K40W03	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 3 N.C. contacts with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$42
SCM2K40X11	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$40
SCM2K40W02	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 2 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$40
SCM2K40X12	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 1 N.O. and 2 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$44
SCM2K40W03	Safety switch, tongue (key) interlock operated, 90 degree adjustable head, 3 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order actuating tongue (key) separately.	\$44
KEY13	Actuator tongue (key) for safety switches, 22mm mounting hole spacing, 90 degree bent mounting tab. Use with SP2K and SDM2K series safety switches	\$2
KEY14	Actuator tongue (key) for safety switches, 22mm mounting hole spacing, straight mounting tab. Use with SP2K and SDM2K series safety switches	\$2
KEY15	Actuator tongue (key) for safety switches, 13mm mounting hole spacing, 90 degree bent mounting tab. Use with SP2K and SDM2K series safety switches	\$2
KEY16	Actuator tongue (key) for safety switches, 13mm mounting hole spacing, straight mounting tab. Use with SP2K and SDM2K series safety switches	\$2
KEY17	Actuator tongue (key) for safety switches, 15mm mounting hole spacing, 90 degree bent shock absorbing mounting tab. Use with SP2K and SDM2K series safety switches	\$4
KEY18	Actuator tongue (key) for safety switches, 15mm mounting hole spacing, straight shock absorbing mounting tab. Use with SP2K and SDM2K series safety switches	\$4
KEY19	Actuator tongue (key) for safety switches, 40mm mounting hole spacing, flexible mounting tab. Use with SP2K and SDM2K series safety switches	\$5
KEY35	Actuator tongue (key) for safety switches, 13mm mounting hole spacing, 90 degree bent mounting tab. Use with SBM2K and SCM2K series safety switches	\$3
KEY36	Actuator tongue (key) for safety switches, 13mm mounting hole spacing, straight mounting tab. Use with SBM2K and SCM2K series safety switches	\$2
KEY39	Actuator tongue (key) for safety switches, 40mm mounting hole spacing, flexible mounting tab. Use with SBM2K and SCM2K series safety switches	\$6
SP2K72X11	Safety switch, shaft hinge interlock operated, 90 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings.	\$33
SP2K72W02	Safety switch, shaft hinge interlock operated, 90 degree adjustable head, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings.	\$33
SP2K61X11	Safety switch, lever hinge interlock operated, 90 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings.	\$22

SP2K61W02	Safety switch, lever hinge interlock operated, 90 degree adjustable head, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings.	\$22
SDM2K72X11	Safety switch, shaft hinge interlock operated, 90 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings.	\$38
SDM2K72W02	Safety switch, shaft hinge interlock operated, 90 degree adjustable head, 2 N.C. contacts with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings.	\$38
SDM2K61X11	Safety switch, lever hinge interlock operated, 90 degree adjustable head, 1 N.O. and 1 N.C. contact with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings.	\$28
SDM2K61W02	Safety switch, lever hinge interlock operated, 90 degree adjustable head, 2 N.C. contacts with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings.	\$28
SDM2K96X11	Safety switch, cable-pull interlock operated, no reset, 1 N.O. and 1 N.C. contact with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$34
SDM2K96W02	Safety switch, cable-pull interlock operated, no reset, 2 N.C. contacts with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$34
SDM2K98X11	Safety switch, cable-pull interlock operated, with reset, 1 N.O. and 1 N.C. contact with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$36
SDM2K98W02	Safety switch, cable-pull interlock operated, with reset, 2 N.C. contacts with slow action break before make, 50mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$36
SBM2K97X11	Safety switch, cable-pull interlock operated, no reset, 1 N.O. and 1 N.C. contact with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$31
SBM2K97W02	Safety switch, cable-pull interlock operated, no reset, 2 N.C. contacts with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$31
SBM2K97X12	Safety switch, cable-pull interlock operated, no reset, 1 N.O. and 2 N.C. contacts with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$34
SBM2K97W03	Safety switch, cable-pull interlock operated, no reset, 3 N.C. contacts with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$35
SBM2K99X11	Safety switch, cable-pull interlock operated, with reset, 1 N.O. and 1 N.C. contact with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$34
SBM2K99W02	Safety switch, cable-pull interlock operated, with reset, 2 N.C. contacts with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$34
SBM2K99X12	Safety switch, cable-pull interlock operated, with reset, 1 N.O. and 2 N.C. contacts with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$37
SBM2K99W03	Safety switch, cable-pull interlock operated, with reset, 3 N.C. contacts with slow action break before make, 40mm wide aluminum body, one conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$38
SCM2K97X11	Safety switch, cable-pull interlock operated, no reset, 1 N.O. and 1 N.C. contact with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$34
SCM2K97W02	Safety switch, cable-pull interlock operated, no reset, 2 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$34

SCM2K97X12	Safety switch, cable-pull interlock operated, no reset, 1 N.O. and 2 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$37
SCM2K97W03	Safety switch, cable-pull interlock operated, no reset, 3 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$37
SCM2K99X11	Safety switch, cable-pull interlock operated, with reset, 1 N.O. and 1 N.C. contact with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$36
SCM2K99W02	Safety switch, cable-pull interlock operated, with reset, 2 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$36
SCM2K99X12	Safety switch, cable-pull interlock operated, with reset, 1 N.O. and 2 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$39
SCM2K99W03	Safety switch, cable-pull interlock operated, with reset, 3 N.C. contacts with slow action break before make, 60mm wide aluminum body, three conduit opening accepts 1/2 inch NPT fittings. Order cable separately.	\$39
FUN05M015	Steel cable for cable-pull safety switches, 15 meter length, 5mm diameter, red plastic coated	\$20
FUN05M025	Steel cable for cable-pull safety switches, 25 meter length, 5mm diameter, red plastic coated	\$31
AP2R11X11	Safety limit switch, pull-reset action, steel plunger actuator, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$20
AP2R11W02	Safety limit switch, pull-reset action, steel plunger actuator, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$20
AP2R13X11	Safety limit switch, pull-reset action, steel plunger with nylon roller actuator, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$21
AP2R13W02	Safety limit switch, pull-reset action, steel plunger with nylon roller actuator, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$21
AP2R31X11	Safety limit switch, pull-reset action, steel plunger with one-way horizontal nylon roller arm lever, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$22
AP2R31W02	Safety limit switch, pull-reset action, steel plunger with one-way horizontal nylon roller arm lever, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$22
AP2R32X11	Safety limit switch, pull-reset action, steel plunger with one-way vertical nylon roller arm lever, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$23
AP2R32W02	Safety limit switch, pull-reset action, steel plunger with one-way vertical nylon roller arm lever, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$23
AP2R41X11	Safety limit switch, pull-reset action, lever with nylon roller actuator, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$25
AP2R41W02	Safety limit switch, pull-reset action, lever with nylon roller actuator, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$25
AP2R51X11	Safety limit switch, pull-reset action, adjustable lever with nylon roller actuator, 1 N.O. and 1 N.C. contact with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$26
AP2R51W02	Safety limit switch, pull-reset action, adjustable lever with nylon roller actuator, 2 N.C. contacts with slow action break before make, 30mm wide plastic body, one conduit opening accepts 1/2 inch NPT fittings	\$26
OCC08	Cable-pull eye bolt for safety switches	\$2
MOR05	Cable-pull cable clamp for safety switches	\$2
RED05	Cable-pull eye thimble for safety switches	\$2

**Warning: Machine safety products sold by AutomationDirect are Safety components only.**

The purchaser/installer is solely responsible for the application of these components and ensuring all necessary steps have been taken to assure each application and use meets all performance and applicable safety requirements and/or local, national and/or international safety codes as required by the application. AutomationDirect cannot certify that our products used solely or in conjunction with other AutomationDirect or other vendors products will assure safety for any application.

Any person using or applying any products sold by AutomationDirect is responsible for learning the safety requirements for their individual application and applying them, and therefore assumes all risks, and accepts full and complete responsibility for the selection and suitability of the product for their respective application.

AutomationDirect does not provide design or consulting services, and cannot advise whether any specific application or use of our products would ensure compliance with the safety requirements for any application.