

	Reduced Voltage Soft Starters	Aust\$
SR22-05	SR22 series Compact Reduced Voltage Soft Starter, 5A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-45 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$210
SR22-07	SR22 series Compact Reduced Voltage Soft Starter, 7A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-45 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$225
SR22-09	SR22 series Compact Reduced Voltage Soft Starter, 9A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-45 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$230
SR22-12	SR22 series Compact Reduced Voltage Soft Starter, 12A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-45 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$245
SR22-16	SR22 series Compact Reduced Voltage Soft Starter, 16A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-45 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$275
SR22-22	SR22 series Compact Reduced Voltage Soft Starter, 22A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-55 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$310
SR22-30	SR22 series Compact Reduced Voltage Soft Starter, 30A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-55 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$420
SR22-36	SR22 series Compact Reduced Voltage Soft Starter, 36A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-55 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$520
SR22-40	SR22 series Compact Reduced Voltage Soft Starter, 40A, 208-230/460 VAC, for 3-phase motors (two phases controlled), rated for 10 starts/hour. (Optional SR22-FAN-55 increases duty cycle to 60 starts/hour.) Three potentiometers control settings for: Start Time, Starting Voltage, and Stop Time (ramps down motor voltage, but does not apply braking torque to a load). Unit may require derating for applications other than fans and pumps; see specifications for appropriate derating. 35mm DIN rail or panel mountable.	\$630
SR22-FAN-45	Cooling fan for SR22 series 45mm soft starters, increases duty cycle to 60 starts/hour for SR22-05, SR22-07, SR22-09, SR22-12, and SR22-16 models. Unit snaps onto bottom of soft starter, includes mounting hardware and connector.	\$75
SR22-FAN-55	Cooling fan for SR22 series 55mm soft starters, increases duty cycle to 60 starts/hour for SR22-22, SR22-30, SR22-36, and SR22-40 models. Unit snaps onto bottom of soft starter, includes mounting hardware and connector.	\$75